



Key Facts

Cast aluminium Al Si 12

IP 66 level of protection

ATEX 100A EEx"e" certification available

High strength low weight

Description - This die cast aluminium enclosure is particularly suitable for the enclosure of a wide range of components, electrical, electronic and pneumatic. The neoprene gasket gives an IP 66 rating.

The enclosure is supplied with earth screws for earthing, the captive lid fixing screws are outside the sealed area.

A range of accessories are available:

Mounting plates, hinges, mounting feet, pole mounting bracket and wire lock screws.

Material - Die cast aluminium Al Si 12

Finish - Stove enamel RAL 7001, unpainted and custom colours available.

Customisation available, to include drilling, milling, engraving and silkscreening.

Order No	A	B	C	D	E	F
EA-50.4530.7001	50	45	30	30.6	40	25
EA-58.6436.7001	58	64	36	34	56	29
EA-75.8057.7001	75	80	57	51.5	72	49
EA-98.6436.7001	98	64	36	75	56	29
EA-12.1280.7001	122	120	80	90	111	72
EA-12.8057.7001	125	80	57	101	72	49
EA-15.6436.7001	150	64	36	126	56	32
EA-16.1690.7001	160	160	90	120	151	82
EA-17.8057.7001	175	80	57	152	72	49
EA-20.2311.7001	200	230	110	160	221	102
EA-22.1280.7001	220	120	80	188	111	72
EA-26.1690.7001	260	160	90	220	151	82
EA-28.1810.7001	280	180	100	240	171	92
EA-33.2311.7001	330	230	110	290	221	102
EA-33.2318.7001	330	230	180	290	218	170
EA-36.1690.7001	360	160	90	316	151	82
EA-40.2311.7001	400	230	110	360	219	102