



Key Facts

ABS or Polycarbonate

IP 66 level of protection

Good chemical resistance

Clear lid option

Description - This range of moulded enclosures are available in either ABS or polycarbonate, which is highly resistant to corrosion, combined with high impact strength and light weight, they are particularly suitable for housing electrical, electronic and control equipment. The neoprene gasket gives an IP 66 rating. Polycarbonate clear lids are available as an option.

A range of accessories are available:

Mounting plates, hinges, mounting feet, and wire lock screws.

Material - ABS or Polycarbonate

Finish - RAL 7035.

Customisation available, to include drilling, milling, engraving and silkscreening.

Order codes - Polycarbonate suffix **-P-**, ABS suffix **-A-**, Clear lid suffix **-T-**

Order No	A	B	C	D	E	F
EM-05.0504.7035	52	50	35	30	45	31
EM-06.0504.7035	65	50	35	43	45	31
EM-08.0805.7035	82	80	55	57	74	49
EM-12.8055.7035	120	80	55	95.2	74	48.5
EM-12.8085.7035	120	80	85	95.2	74	80
EM-16.8055.7035	160	80	55	135	74	48.5
EM-16.8085.7035	160	80	85	135	74	80
EM-12.1255.7035	122	120	55	97.2	114	50
EM-12.1285.7035	122	120	85	97.2	114	79
EM-16.1290.7035	160	120	90	135.2	114	83.5
EM-20.1275.7035	200	120	75	175.2	113	67.5
EM-20.1575.7035	200	150	75	175	144	69
EM-24.1210.7035	240	120	100	217.4	114	94
EM-24.1690.7035*	240	160	90	217.4	154	84
EM-24.1612.7035*	240	160	120	217.4	154	114
EM-30.2311.7035*	300	230	110	275	224	103
EM-36.2015.7035*	360	200	150	320	191	144

Enclosures marked * have six lid fixing, no of mounting bushes dependant on size